

TECHNICAL DATA SHEET

Description: **Ruichem[®] RC-918** is a rutile titanium dioxide pigment, produced by the sulfate process. It is designed for top grade masterbatch, etc.

Key features:

- Supports the production of highly loaded pigment concentrates
- High dispersion (low FPV value)
- High opacity, high brightness with blue tone
- High reducing strength with blue undertone
- Outstanding lacing resistance

Applications:

- ★ Polyethylene / polypropylene masterbatches
 - Injection molding
 - Blow molding
 - Blown film
- ★ General purpose polystyrene and ABS
- Rigid and flexible PVC, interior
- Other engineering plastics

Remarking: ★ Highly Recommended; ● Recommended

Properties:

• TiO ₂ content:	≥97.0%
• Inorganic coating:	Al
• Organic treatment:	Present
• Specific gravity:	4.1
• Average particle size, um:	0.25~0.30
• Loss at 105℃:	≤0.30%
• Oil absorption, g/100g:	≤16.0
• ISO591-1:2000(E):	R1

Package & storage:

Package: 25kgs craft paper bag, or 500kgs/1000kgs plastic woven bag.

Storage: Keep tightly sealed and stored in a cool, dry and well-ventilated area.

Headquarters

Hangzhou Ruijiang Chemical Co., Ltd
Add: Floor 12th, No.99, Huaxing Road,
Hangzhou, Zhejiang, China
Tel: +86-571-28023733
Fax: +86-571-88930225
E-mail: ruichem06@ruijianggroup.com

HK Branch

Hangzhou Ruijiang
Chemical Co., Limited
Room 2105 HZ2555
Trend Centre 29-31
Cheung Lee Street
Chai Wan HK

European Branch

Ruichem Europe B.V.
Beursplein 37, 3011AA
Rotterdam

USA Branch

RUICHEM USA, INC.
99 Wall Street, Suite
2866, New York, NY
10005, USA

Website: www.ruitio2.com

Note: The information herein is believed to be reliable. However, no warranty, expressed or implied, is made as to its accuracy or completeness and none is made as to the merchantability of the material or its fitness for any purpose. The manufacturer shall not be liable for consequential damages or for damages to persons or property resulting from its use. Nothing herein shall be construed as a recommendation for use in violation of any patent.